

Discos Disponibles para el WaterLink Spin Touch

Aplicación: Piscinas/Spas	Código	4328	4329	4330	4331	4334	4335	4340
	Serie #	103	203	303	402	501	601	701
	Usos por disco	1	1	1	1	3	3	3
Parámetro	Rango							
Cloro libre	0-15 ppm	•	•	•		•	•	•
Cloro total	0-15 ppm	•	•	•		•		
Bromo	0-33 ppm	•	•	•		•	•	•
pH	6.4-8.6	•	•	•	•	•	•	•
Dureza cálcica	0-800 ppm	•	•	•	•			
Alcalinidad total	0-250 ppm	•	•	•	•		•	
Ácido cianúrico	5-150 ppm	•	•	•				•
Cobre	0-3.0 ppm	•	•	•	•			
Hierro	0-3.0 ppm	•	•	•	•			
Sal	0-5,000 ppm	•	•	•				
Fosfato	0-2,000 ppb		•					
Borato	0-80 ppm			•	•			
Biguanida	0-70 ppm				•			
Choque de biguanida	0-250 ppm				•			

Aplicación: Agua Potable y de Pozos	Código: 4336	Código: 4337
	Serie #: DW13	Serie #: DW21
	Usos por disco: 1	Usos por disco: 1
Parámetro	Rango	
Cloro libre	0-15 ppm	
Cloro total	0-15 ppm	
Cloro combinado	0-15 ppm	
pH	6.4-10.0	4.5-8.6
Dureza Total	0-70 gpg, 0-1,200 ppm	0-70 gpg, 0-1,200 ppm
Hierro total	0-6 ppm	0-6 ppm
Ion férrico		0-6 ppm
Ion ferroso		0-6 ppm
Cobre	0-6 ppm	0-6 ppm
Nitrato (NO ₃)		0-45 ppm
Nitrito (NO ₂)		0-2 ppm
Alcalinidad total	0-250 ppm	0-250 ppm

WaterLink **SpinTouch**

LaMotte  **Watertest Solutions**
Solving Analytical Challenges Since 1919

